


VERIFICATION OF NUMERICALLY CONTROLLED MACHINE PROGRAMS BY THE AUTOMATIC DRAFTING MACHINE

D. CONCORDIA

March 1977





WATERVLIET ARSENAL
WATERVLIET, N.Y. 12189

TECHNICAL REPORT

AMCMS No. 3297.06.7484 PRON No. M1-4-A1559(01) M7-M7

AD NO.

APPROVED FOR PUBLIC RELEASE: DISTRIBUTION UNLIMITED

DISCLAIMER

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) in this report does not constitute an official indorsement or approval.

DISPOSITION

Destroy this report when it is no longer needed. Do not return it to the originator.

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered) READ INSTRUCTIONS REPORT DOCUMENTATION PAGE BEFORE COMPLETING FORM RECAPIENT'S CATALOG NUMBER 2. GOVT ACCESSION NO. PORT NUMBER WVT-TR-77011 YPE OF REPORT & PERIOD COVERED VERIFICATION OF NUMERICALLY CONTROLLED MACHINE PROGRAMS BY THE AUTOMATIC DRAFTING MACHINE. 8. CONTRACT OR GRANT NUMBER(#) AUTHOR(s) D. Concordia 10. PROGRAM ELEMENT, PROJECT, TASK AREKS NO. 3297, 06.7484 9. PERFORMING ORGANIZATION NAME AND ADDRESS Benet Weapons Laboratory V Watervliet Arsenal, Watervliet, N.Y. 12189 PRON No.MJ-4-A1559(01)M7-M7 SARWV-RT-TP REPORT DATE 11. CONTROLLING OFFICE NAME AND ADDRESS March 1977 US Army Armament Research and Development Command 43. NUMBER OF PACE 48 Dover, New Jersey 07801 14. MONITORING AGENCY NAME & ADDRESS(If different from Controlling Office) 15. SECURITY CLASS. (of this report) UNCLASSIFIED 15a. DECLASSIFICATION/DOWNGRADING SCHEDULE 16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited. 17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report) 18. SUPPLEMENTARY NOTES 19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Numerical Control Automatic Drafting Machine 20. ABSTRACT (Continue on reverse side if necessary and identity by block number) This is a report on the modifications made to the Gerber automatic drafting program to allow for the verification of numerical controlled machine programs on the automatic drafting machine. Programming changes were made so that the eleven most-used machines at Watervliet Arsenal can be verified.

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered

TABLE OF CONTENTS

		Page
Introduction		1
Bostomatic Incremental		2
Bostomatic Absolute		4
LeBlonds		9
Cincinnati Hydrotel		10
Bullard VTL		11
CIMX-720, CIM-X-A6		11412
XLO Chuckers		12
Cincinnati Turning Center	The second second	13
Conclusion	Hills Britis Straigs C	13
Appendix A	010	14
Appendix B	MENTASPRICE	15-31
	BY	32
Appendix C	DIST. AVAILABLE SPECIAL	33-36
Appendix D		37
Appendix E		38-39
Appendix F		
Appendix G		40-46
Appendix H	A TOTAL ON	47
	ILLUSTRATION	
Figure 1 Flow Chart		6

INTRODUCTION

Watervliet Arsenal has a large variety of makes of numerically controlled (N.C.) machines. For about the past three years a Gerber automatic drafting machine (ADM), with a Honeywell 316 mini-computer control, has been used to verify the N/C tapes. Unfortunately, no universal language exists for the programming of all N.C. machines and in fact almost all manufacturers differ in the programming for their machines. The Gerber (ADM) method of programming obviously could not allow the verification of all types of N.C. machines.

In the fall of 1975, a meeting of ADM and NC programming personnel was held and it was concluded that an attempt would be made at modifying the existing Gerber drafting program so that different NC machines could be verified. A priority list of eleven makes of machine based on usage, was compiled which included the following:

- 1. Bostomatic vertical spindle mill
- 2. LeBlond CXR horizontal lathe (small components)
- 3. LeBlond horizontal lathe (tubes)
- 4. Pratt & Whitney Wolverine vertical spindle mill
- 5. Lodge & Shipley Lathe
- 6. Cincinnati Hydrotel vertical spindle mill
- 7. Bullard VTL vertical lathe
- 8. CIM-X 720 horizontal spindle mill and drill
- 9. CIM-X A6 horizontal spindle mill and drill
- 10. XLO Chucker vertical lathe
- 11. Cincinnati Turning Center horizontal lathe

Changes to the existing program were completed by 1 January 1976 enabling the verification of the eleven machines. A description follows, of the changes made for 9 of the 11 machines since the Pratt & Whitney Wolverine and the Lodge and Shipley tapes could already be verified

with the Gerber drafting program without changes. All changes made appear in appendices A-H, written in the Honeywell assembly language, with comments in the right hand column.

It should be pointed out that parameters used for each machine were also incorporated in the program for each particular machine. In this way, when the program for a particular machine is loaded, the correct parameters are included. Parameters differing from one machine to another include the format statement for the coordinate values and the axis select, which allow selecting X, Y or Z for the horizontal and vertical axis.

BOSTOMATIC

Incremental

The Bostomatic machine may operate in either the absolute or incremental modes (i.e., with coordinate values either referenced to a fixed zero position or referenced to the present position of the pen). The changes required for the incremental mode were minor. They included the following:

- 1. Read a G1, G2, G3 command as a G01, G02, G03.
- 2. Read only Code GO1, GO2, GO3, G40, G41, G42 and ignore any other G code. Read a G40, G41, G42 as a GO1.

The G command instructs the machine to move either linearly (GO1) or in a circular motion (GO2 clockwise, GO3 counter-clockwise). As the Gerber program existed a G1 would be read as a G10, which is the code to draw linearly, but at a scale ten times.

The change involved only one instruction, which was eliminated from the program since this instruction made the assumption that zero was the second digit of any G code by shifting the contents of the memory location holding the G code number left 4 positions. This memory location stores the number, in base two, so shifting left would fill the 4 right most memory bits with zeros.

The interpreting of a G code by the Gerber program is done in the following manner. At a particular point in the program, the A register (the working register of the computer) contains the G number in coded form. For example, if a 60 were the G code, the number in the A register would be an octal 140 or in binary, a 01 100 000. The first four bits, starting from the right, contain the right most digit of the G code, in this case, a zero. Since this number could be as great as a nine in decimal, which would be 1001 in binary, four bits are required to store the right most number of the G code. The next four bits, 5 through 8, contain the left hand number of the G code, in this example, a six. The G code is now compared to the coded form of a G number already stored in a certain location in memory. If the numbers are equal, the program jumps to the appropriate place in the programs which executes the command based on the particular G code used. In the example used here, a G60, which is the code to move linearly at a scale of 100, the program would go to that place in the program which executes the command at a scale 100 times the values given. If the G code should be greater or less than the number to

which it is being compared, the program could take either of two paths. It would either compare the G code to the next lower coded number in memory or would interpret the code based on the fact that it is greater than one number but less than another. As far as changes made so that G codes for the Bostomatic Incremental tape would be read correctly, the appropriate comparisons were made, replacing the ones which already existed. For example, to read a G42 as a G01, the A register, which would contain the coded form of a 42 (1000010), would be compared to a memory location which contains a coded 42. They would be equal so the program would jump to the place in the program which makes a linear move since it was desired to read a G42 as a G01. Changes made to allow for the running of a Bostomatic Incremental tape appear in Appendix A.

BOSTOMATIC

Absolute


The changes made to the Gerber program to accommodate the running of a Bostomatic absolute N.C. tape included the following:


- 1. Read only a GO1, GO2, GO3, G40, G41, G42 and ignore any other command. Read a G40, G41, G42 as a GO1.
 - 2. Read a G1, G2, G3 as a G01, G02, G03.
- 3. Read the I, J number of a circular command in the appropriate way.

The changes for Items 1 and 2 are the same as for the Bostomatic Incremental and are explained under that section. The changes needed for the correct reading of a circular command on a Bostomatic absolute tape, Item 3, will now be given.

A circular command requires four different numbers X, Y, I, and J values. For the Gerber program, the X and Y values are the coordinates of the end point of the arc being drawn. The I and J are horizontal and vertical distances respectively from the arc center to the starting point of the arc. The Bostomatic X and Y values are the same as the Gerber but the I and J are the coordinates of the center of the arc relative to zero position. The changes needed to accommodate this difference became rather involved. A flow chart (Fig. 1) is included to help explain the programming. The chart shows the program for calculating a new I value. The programming for calculating a new J is the same except all X and I are replaced by Y and J. The basic approach of the programming was to subtract the Bostomatic I (or J) value from the previous X (or Y) value to obtain the incremental distance from the center of the arc to the starting point, which is the value needed for I (or J) in the Gerber program (in some cases, such as when the I value is negative and the previous X value positive, the two values would be added to obtain the new I value).

In order to explain the programming changes, the manner of storing a decimal number in memory should be explained. The Gerber system allows for a number with up to three places to the left of the decimal point and five to the right. The number is stored in two memory locations with each location having 15 bit positions, plus a bit position for the sign. A zero is stored with all bit positions containing zero. The number .00001 would contain the binary number 000 000 000 000 001,





the number .00002 would be stored as the binary number 000 000 000 000 010. The number .00003 would appear as 000 000 000 000 011 or in other words, the binary number 3 (11). This method of storing the number continues until the memory location contains 111 111 111 111 111 111 at which time increasing the number by .00001 would store a 1 in the other memory location and return this location to all zeros. As the number increased still further, this location would again increase until it contained all ones, at which time a further increase of .00001 would again add one to the other memory location, making it a 10 and return the location containing all ones to all zeros. A negative number is stored as the complement of the most significant part of the number and the two's complement of the least significant part.

Referring now to Figure 1, when an I value is found, this value is stored and tests are made to see if X and I are negative. If they are negative, they are set positive by complementing the number since it is desired to work with only positive numbers. If the I and X values have opposite signs they are added to obtain the incremental distance from the center of the arc to the starting point. With the same sign for X and I values, the smaller number is subtracted from the larger to obtain the incremental distance desired. When the adding or subtracting is done, the program then returns to the main program with the newly calculated form of I (or J) in a particular memory location. The Gerber program can now operate on the circular command with the I (or J) value in the form required (see Appendix B).

The subtraction process used in the programming requires some explanation. The most significant part of the smaller number is first subtracted from the most significant part of the larger number. The least significant parts of the two numbers are then compared. If the most significant parts had been equal, the smaller of the least significant parts of the two numbers is subtracted from the larger. Otherwise, if the least significant part of the one number is less than the least significant part of the other number, but its most significant part is less, the sign bit of the smaller least significant part number is set to one. A one is then subtracted from the most significant part of the number and the two least significant parts are then subtracted.

To make a negative number (a number with a sign bit in its most significant part of one) positive, the two complement of the least significant part is taken and the complement of the most significant part. The one exception is if the least significant part of the number is zero, in which case, the two complement of the most significant part is taken.

LeBlond and LeBlond CXR

Both LeBlond machines required similar changes to facilitate the verification of the tapes. The changes included the following:

Treat G92, G33, G34, G35, as a G01; ignore other G commands except G01, G02, G03.

The programming needed for these changes was similar to the G code changes made for the Bostomatic Incremental, which are described

under that section. One additional programming change was required because of a peculiarity which occurred with the GO4 command. This command occurs in the LeBlond tape but for verification purposes, it was desired to ignore it. The GO4 code is a modal command, meaning if GO4 is given, any statement following, without a G code, is assumed GO4. By ignoring GO4, no G number is stored in memory so, when modality occurs with the GO4, the program finds no G number for the statement and assumes an error, which is not the desired result. To correct this, a 4 was put into the G number memory location each time a GO4 occurred (see Appendix C).

Cincinnati Hydrotel

The Cincinati Hydrotel required the following programming changes:

- Circular command I, J, values defined same as for Bostomatic Absolute.
 - 2. Two statements required to define an arc.

The first change was the same as for the Bostomatic Absolute and is given under that section. The defining of an arc with two statements is done in the following manner. The first statement has a GO2 or GO3 code, with an X and Y, followed by a value. These values are the I and J values (the distance from coordinate zero to the center of the arc) for the arc being programmed. The X and Y, which are used here, could be replaced by an I and J. The next statement would not have a G code, only an X and Y, followed by a value. These values

are the coordinate of the end point of the arc being programmed.

The approach used to accomplish these changes was done in the following manner. When a GO2 or GO3 was encountered, a one was stored in a particular memory location. Otherwise, a zero is stored at this location. When an X or Y is encountered, this location is checked and if it is one, the X or Y is changed to an I or J. In this way, the program thinks it has an I or J value and this value is then stored in memory. Upon encountering the next statement, it is assumed circular and the X and Y values, along with the I and J values stored from the previous statement, are used in executing the circular command (see Appendix D).

BULLARD VTL

The change needed for the Bullard VTL was minor requiring only that a GO3 command be a clockwise circular command and a GO2, a counter-clockwise circular command. The Gerber program interpreted a GO3 as counter-clockwise and a GO2 as clockwise (see Appendix E).

CIM-X-720

The CIM-X-720 required changes identical to the Bostomatic Absolute except for a difference in interpreting I and J values. The CIM-X-720 I and J values are modal, meaning if an I or J is omitted from a statement, its value is assumed the same as the value for I or J in the previous statement. The Bostomatic differed in

that if an I or J value is omitted, it assumes an X or Y value of the previous statement for the value of I or J.

The approach used in the programming was to simply store I and J values each time they were found and then reload in the proper location whenever a new statement is encountered. In this way, If a statement is a circular command and an I or J is omitted, the previous I or J will already be in the proper memory location (see Appendix F).

CIM-X-A6

The CIM-X-A6 changes were the same as the ones made for the Bostomatic Absolute and CIM-X-720 except for the way a G93 code is interpreted. The G93 has a B value which is used as an X value except it is multiplied by a factor of 29.5719. To program for this change, if a G93 code is encountered, it has the B changed to an X. The scale factor for the machine for the X axis is then changed to 29.5719. The command is then executed and the scale factor is changed back to one. At the same time, a one is stored in a particular memory location. In this way, if the following statement after a G93 has a G code this particular memory location is checked and if it is a one, the scale factor for the X axis is again changed to 29.5719 (see Appendix G).

XLO Chuckers

The XLO Chucker change was the same as for the Bullard VTL and is explained under that section (see Appendix E).

Cincinnati Turning Center

The Cincinnati Turning Center programming uses a plus or minus sign before I or J values whereas the Gerber program does not use a sign before I or J values. If a minus sign is used the program will output an error. To correct this at the point in the program where an I or J value is encountered, a check is made to see if the next character is a minus. If it is minus, it is replaced by a plus sign which will allow the correct reading of the program in the Gerber format (see Appendix H).

CONCLUSION

The verifying of numerical control tapes by the automatic drafting machine has proven a feasible means of finding errors in programs. With the ability to verify the eleven most used machines at Watervliet Arsenal, the process has become much more useful. The modification of the Gerber drafting program has shown that the capability exists to change the program to accommodate any make of N.C. machine. The modifications necessary to verify the remaining N.C. machine can thus be made as the need arises.

APPENDIX A

BOSTOMATIC (INCREMENTAL)

LOCATION	INSTRUCTION	COMMENT
2205	NOP	Read Gl etc. as GO1 etc.
To read only GO1, GO2, command.	G03, G40, G41, G42 and	ignore any other G
2212	CAS = '102	Compare 42
2213	JMP* '505	
2214	JMP 2261	
2215	CAS = '100	Compare 40
2216	JMP 2261	
2217	JMP 2261	
2220	JMP 2253	
2230	DAC '102	
2231	DAC '100	

APPENDIX B

BOSTOMATIC ABSOLUTE (For I)

LOCATION	INSTRUCTION	COMMENT
15205	JST* 15675	
15211	JST* 15676	
15232	JST* 15676	
15335	JST* 15675	
15675	12026	
15676	12041	
12026	000000	
12027	LDA* 12054	
12030	CAS 133	Changes take the two's complement
12031	JMP' 12033	of the most significant part of I, X values,
12032	JMP 12036	if it is negative and if its least signi-
12033	LDA* 12055	ficant part is 0.
12034	CMA	
12035	JMP* 12026	
12036	LDA* 12055	
12037	TCA	
12040	JMP* 12026	
12041	000000	
12042	IAB	
12043	CAS 133	
12044	JMP 12046	

INSTRUCTION

COMMENT

LOCATION

			-
12045	JMP 1	2051	
12046	IAB		
12047	CMA		
12050	JMP* 1	2041	
12051	IAB		
12052	TCA		
12053	JMP* 1	2041	
12054	15451		
12055	15450		
Changes to Bostomatic Absol G40 pen up.	ute prog	gram so G41, 42 will n	nake pen down,
2214	JMP 2	2232	If G42
2216	JMP 2	232	If G41
2217	JMP 2	2235	If G40
2232	LDA 1	(160)	Load 232 (pen position)
2233	STA 2	232	with 1.
2234	JMP 2	2261	
2235	LDA 2	2 (225)	Load 232 (pen position)
2236	STA 2	232	with 2.
2237	JMP 2	2261	
2205	NOP 1	.0100	Read G1 etc. as G01 etc.
774	DAC 2	2650	
2511	DAC 1	5400	
2120	JMP∗ 2	2511	
15400	STA 1	5452	Store A

LOCATION	INSTRUCTION	COMMENT
15401	LDA 323	Store previous
15402	STA 775	Y in 775 most sig. 773 least sig.
15403	LDA 324	
15404	STA 773	
15405	LDA 321	Store previous X in 450 most sig.
15406	STA 15450	451 least sig.
15407	LDA 322	
15410	STA 15451	
15411	JMP 15433	
15433	LDA 15452	Reload A
15434	NOP	
15435	JMP* 774	Jump back
777	DAC 15150	
2516	JST* 777	
15150	PZE	
15151	JMP 15360	
15152	IAB	Make least sig. part
15153	TCA	I pos. if it was neg.
15154	SSP	
15155	IAB	
15156		
13130	STA 15320	

LOCATION	INSTRUCTION	COMMENT
15160	SMI	Check if X is neg.
15161	JMP 15204	
15162	LDA 451	
15163	TCA	Make least sig. part
15164	SSP	of X positive.
15165	STA 15451	
15166	LDA 15320	
15167	JMP 15230	
15170	STA 15320	
15171	LDA 15450	
15172	SPL	
15173	JMP 15176	
15174	LDA 15320	
15175	JMP 15230	
15176	STA 15321	
15177	LDA 15451	
15200	TCA	
15201	SSP	
15202	STA 15451	
15203	LDA 15450	
15204	SPL	Check most sig. part of X, I
15205	CMA .	01 A, 1
15206	STA 15450	

LOCATION	INSTRUCTION	COMMENT
15207	LDA 15320	
15210	SPL	
15211	CMA	
15212	ADD 15450	
15213	STA	
15214	IAB	If X and I have opposite
15215	ADD 15451	signs add them subtract them.
15216	SMI	Subtract them.
15217	JMP 15226	
15220	SSP	
15221	STA CAPI+1	
15222	LDA CAPI	
15223	ADD = 1	
15224	STA CAPI	
15225	JMP* 15150	
15226	STA CAPI+1	
15227	JMP* 15150	
15230	SMI	
15231	JMP 15233	If X and I are both positive or
15232	CMA	negative sign.
15233	STA 15320	
15234	LDA 15450	
15235	SMI	

LOCATION	INST	TRUCTION	COMMENT
15236	JMP	15240	
15237	JMP	15335	
15240	CAS	15320	
15241	JMP	15550	
15242	JMP	15514	
15243	LDA	15320	
15244	SUB	15450	
15245	STA	CAPI	
15246	IAB		Subtract them
15247	CAS	15451	
15250	JMP	15303	
15251	JMP	15303	
15252	SSM		
15253	SUB	15451	
15254	STA	CAPI+1	
15255	LDA	CAPI	
15256	SUB	=1	
15257	JMP	15330	
15261	SUB	15320	
15262	STA	CAPI	
15263	IAB		
15264	STA	15501	
15265	LDA	15451	

LOCATION	INSTRUCTION	COMMENT
15266	CAS 15501	
15267	JMP 15300	
15270	JMP 15300	
15271	SSM	
15272	SUB 15501	
15273	STA CAPI+1	
15274	LDA CAPI	
15275	SUB =1	
15276	STA CAPI	
15277	JMP* 15150	
15300	SUB 15501	
15301	STA CAPI+1	
15302	JMP* 15150	
15303	SUB 15451	
15304	STA CAPI+1	
15305	JMP* 15150	
15360	STA 15470	
15361	IAB	Store I value
15362	STA 15471	
15363	IAB	Check if I is neg.
15364	SMI	if it is, make least sig. part of number
15365	JMP 15170	positive, up to 204

LOCATION	INSTRUCTION	COMMENT
15366	JMP 15152	
15335	CMA	
15336	STA 15450	
15337	JMP 15240	These statements
15330	STA CAPI	placed here because contents would not
15331	JMP* 15150	stay in location 15260
15514	SUB 15320	
15515	STA CAPI	
15516	IAB	
15517	CAS 15451	
15520	JMP* +1	
15521	JMP 15527	
15522	STA 15501	
15523	LDA 15451	
15524	SUB 15501	
15525	STA CAPI+1	
15526	JMP* 15150	
15527	SUB 15451	
15530	STA CAPI+1	
15531	JMP* 15150	
15550	SUB 15320	
15551	STA CAPI	

LOCATION	INSTRUCTION	COMMENT
15552	IAB	
15553	STA 15501	
15554	LDA 15451	
15555	CAS 15501	
15556	JMP 15300	
15557	JMP 13300	
15560	SSM	
15561	SUB 15501	
15562	JMP 15273	

APPENDIX B
BOSTOMATIC ABSOLUTE (For J)

LOCATION	INSTRUCTION	COMMENT
15035	JST* 15673	
15041	JST* 15674	
15062	JST* 15674	
15340	JST* 15673	
15673	12000	
15674	12013	
12000	000000	
12001	LDA 773	
12002	CAS 133	
12003	JMP 12005	Changes take the
12004	JMP 12010	two's complement of the most signi-
12005	LDA 775	ficant part of J, Y values, if it is
12006	CMA	negative and if its least significant
12007	JMP* 12000	part is O.
12010	LDA 775	
12011	TCA	
12012	JMP* 12000	
12013	000000	
12014	IAB	

LOCATION	INSTRUCTION	COMMENT
12015	CAS 133	
12016	JMP 12020	
12017	JMP 12023	
12020	IAB	
12021	CMA	
12022	JMP* 12013	
12023	IAB	
12024	TCA	
12025	JMP* 12013	
776	DAC	
776		
2512	JST* 776	
15000	PZE	
15001	JMP 15370	
15002	IAB	Make least sig.
15003	TCA	part Y and J
15004	SSP	positive if they were negative.
15005	IAB	
15006	STA 15320	*
15007	LDA 775	
15010	SMI	
15011	JMP 15034	

LOCATION	INSTRUCTION	COMMENT
15012	LDA 773	
15013	TCA	
15014	SSP	
15015	STA 773	
15016	LDA 15320	
15017	JMP 15060	
15020	STA 15320	
15021	LDA 775	
15022	SPL	
15023	JMP 15026	
15024	LDA 15320	
15025	JMP 15060	
15026	STA 15321	
15027	LDA 773	
15030	TCA	
15031	SSP	
15032	STA 773	
15033	LDA 15321	
15034	SPL	
15035	CMA	Add Y and J
15036	STA 775	if both are positive or
15037	LDA 15320	both negative.

LOCATION	INSTRUCTION	COMMENT
15040	SPL	
15041	CMA	
15042	ADD 775	
15043	STA CAPJ	
15044	IAB	
15045	ADD 773	
15046	SMI	
15047	JMP 15056	
15050	SSP	
15051	STA CAPJ+1	
15052	LDA CAPJ	
15053	ADD =1	
15054	STA CAPJ	
15055	JMP* 15000	
15056	STA CAPJ+1	
15057	JMP* 15000	
15060	SMI	Subtract smallest
15061	JMP 15063	from largest if J and Y have opposite
15062	CMA	values.
15063	STA 15320	
15064	LDA 775	
15065	SMI	

LOCATION	INSTR	RUCTION	COMMENT
15066	JMP	15070	
15067	JMP	15340	
15070	CAS	15320	
15071	JMP	15111	
15072	JMP	15532	
15073	LDA	15320	
15074	SUB	775	
15075	STA	CAPJ	
15076	IAB		
15077	CAS	773	
15100	7110	15.00	
15100	JMP	15133	
15101	JMP	15133	
15102	SSM		
15103	SUB	773	
15104	STA	CAPJ+1	
15105	LDA	CAPJ	
15106	SUB	=1	
15107	STA	CAPJ	
15110	JMP*	15000	
15111	SUB	15320	
15112	STA	CAPJ	

LOCATION	INSTR	UCTION	COMMENT
15113	IAB		
15114	STA	15501	
15115	LDA	773	
15116	CAS	15501	
15117	JMP	15130	
15120	JMP	15130	
15121	SSM		
15122	SUB	15501	
15123	STA	CAPJ+1	
15124	LDA	CAPJ	
15125	SUB	=1	
15126	STA	CAPJ	
15127	JMP*	15000	
15130	SUB	15501	
15131	STA	CAPJ+1	
15132	JMP*	15000	
15133	SUB	773	
15134	STA	CAPJ+1	
15135	JMP*	15000	
	C144		
15340	CMA		
15341	STA	775	

LOCATION	INSTRUCTION		COMMENT
15342	JMP	15070	
15370	STA	15472	
15371	IAB		
15372	STA	15473	
15373	IAB		
15374	SMI		
15375	JMP	15020	
15376	ЈМР	15002	
2510	JMP	2512	
2517	NOP	2312	
2520	NOP		
2320	NOT		
15532	SUB	15320	
15533	STA	CAPJ	
15534	IAB		
15535	cas	773	
15536	JMP*	+1	
15537	JMP	15545	
15540	STA	15501	
15541	LDA	773	
15542	SUB	15501	
15543	STA	CAPJ+1	

LOCATION	INSTRUCTION	COMMENT
15544	JMP* 15000	
15545	SUB 773	
15546	JMP* 15000	
15547	JMP* 15000	
To read only GO1, GO2, G	03, G40, G41, G42	
2212	CAS = 102	Compare 42
2213	JMP* '505	
2214	JMP 2261	
2215	CAS = 100	Compare 40
2216	JMP 2261	
2217	JMP 2261	
2220	JMP 2253	
2230	DAC '102	
2231	DAC '100	
2254	JMP* '505	

APPENDIX C

LEBLOND

LOCATION	INSTRUCTION	COMMENT
2777	222	G92 treat G01,
2213	JMP* 505	greater G92 ignore G33, 34, 35 treat G01 G25, 26 ignore
2214	JMP 2261	G01 G25, 26 1gHore
2232	JMP 2261	
2241	JMP 1075	
2255	JMP 2313	If GO4 load 2332 with a 4.
2313	LDA 2331	with a 4.
2314	STA 2332	
2315	JMP* 505	
2722	JMP 2316	
2316	LDA 2332	If ERNG error about to be printed check
2317	CAS 2331	in GO4 mode, if yes, do not print ERNG.
2320	JMP 2741	do not print bato.
2321	JMP* 505	
2322	JMP 2741	
2331	DAC 4	
2104	JMP 2323	If G code other than
2323	CRA	GO4, make 2332 zero so ERNG will print.
2324	STA 2332	30 Elino will print.
2325	JMP 2170	

APPENDIX D

CINCINNATI HYDROTEL

(Changes to Bostomatic Absolute Drafting Program)

LOCATION	INSTRUCTION	COMMENT
2242	15600	
2277	JMP* 2242	
15600	STA 15605	
15601	LDA 160	If CO2 CO7 -tone
15602	STA 15606	If G02, G03 store a 1.
15603	LDA 15605	
15604	JMP* 15607	
15605	Temp storage for A	
15606	000000	
15607	2351	
2212	JMP 2253	
2254	JMP* 50S	
2244		Audio John
2244 2070	15610 JMP* 2244	Axis date Check if GO2, GO3 if yes go 15620, if no go 15647.
15610	STA 15605	11 no go 13047.
15611	LDA 15606	
15612	CAS 160	
15613	JMP 15615	
15614	JMP 15620	
15615	JMP 15647	

LOCATION	INST	RUCTION	COMMENT
15620	LDA	15605	
15621	CAS	167	Compare with X
16522	JMP	15624	No
15623	JMP	15627	Yes
15624	LIA	221	Make it a J
15625	JMP*	15626	
15626	2500		
15627	LDA	271	Make it an I
15630	JMP*	15626	
2245	1563	1	
2261	JMP*	2245	
15631	STA	15605	
15632	LDA	133	If GO1, store O
15633	STA	15606	
15634	LDA	15605	
15635	JMP	703	
15435	JMP	15636	
13433	OM	13030	
15636	LDA	304	Stone mariana I
15637	STA	15570	Store previous I, J.
15640	LDA	305	

LOCATION	INST	RUCTION	COMMENT
15641	STA	15571	
15642	LDA	306	
15643	STA	15572	
15644	LDA	307	
15645	STA	15573	
15646	JMP	15663	
15647	NOP		
15650	LDA	15570	
15651	STA	304	
15652	LDA	15571	Load previous I, J.
15653	STA	305	
15654	LDA	15572	
15655	STA	306	
15656	LDA	15573	
15657	STA	307	
15660	LDA	15605	
15661	JMP*	15662	
15662	2430		
15663	LDA	15606	
15664	CAS	160	
15665	JMP	15667	
15666	JMP	15670	

LOCATION	INSTRUCTION	COMMENT
15667	JMP* 774	
15670	LDA 133	
15671	STA 15606	
15672	JMP* 505	

APPENDIX E BULLARD VTL

LOCATION INSTRUCTION COMMENT 2257 JMP 2275 2260 JMP 2276

APPENDIX F

CIM-X-720
(Changes to Bostomatic Absolute Program)

LOCATION	INSTRUCTION	COMMENT
To make I, J, modal		
15435	JMP 15600	
15600	LDA 304	
15601	STA 15570	
15602	LDA 305	
15603	STA 15571	
15604	LDA 306	
15605	STA 15572	
15606	LDA 307	
15607	STA 15573	
15610	JMP* 774	
2331	15611	
2070	JMP* 2331	
15611	STA 15670	
15612	LDA 15570	
15613	STA 304	
15614	LDA 15571	
15615	STA 305	
15616	LDA 15572	

LOCATION	INSTRUCTION	COMMENT
15617	STA 306	
15620	LDA 15573	
15621	STA 307	
15622	LDA 15670	
15623	JMP* 15624	
15624	2430	
2230	' 160	
2213	JMP 703	****
2214	JMP 703	If 70 or greater
2215	JMP 2253	treat as GO1.

APPENDIX G

CIM-X-A6 (Changes to Bostomatic Absolute Program)

LOCATION	INSTRUCTION	COMMENT
15435	JMP 15600	
15600	LDA 304	
15601	STA 15570	To make I, J, K,
15602	LDA 305	modal.
15603	STA 15571	
15604	LDA 15306	
15605	STA 15572	
15606	LDA 307	
15607	STA 15573	
15610	JMP* 774	
2331	15611	
2331	15611 JMP* 2331	
2331 2070	15611 JMP* 2331	
2070	JMP* 2331	
2070 15611	JMP* 2331 STA 15670	
2070 15611 15612	JMP* 2331 STA 15670 LDA 15570	
2070 15611 15612 15613	JMP* 2331 STA 15670 LDA 15570 STA 304	
2070 15611 15612 15613 15614	JMP* 2331 STA 15670 LDA 15570 STA 304 LDA 15571	
2070 15611 15612 15613 15614	JMP* 2331 STA 15670 LDA 15570 STA 304 LDA 15571 STA 305	
2070 15611 15612 15613 15614 15615	JMP* 2331 STA 15670 LDA 15570 STA 304 LDA 15571 STA 305 LDA 15572	
2070 15611 15612 15613 15614 15615 15616	JMP* 2331 STA 15670 LDA 15570 STA 304 LDA 15571 STA 305 LDA 15572 STA 306	

LOCATION	INSTRUCTION	COMMENT
15622	LDA 15670	
15623	JMP* 15624	
15624	2430	
2235	STA 2301	
2236	LDA 2300	If G93 replace B by X.
2237	CAS 101 (1)	replace b by x.
2240	JMP 2242	
2241	JMP 2244	
2242	LDA 2301	
2243	JMP 2064	
2244	LDA 2301	
2245	CAS 242 (B)	
2246	JMP 2064	
2247	JMP 2251	
2250	JMP 2064	
2251	LDA 167 (X)	
2252	JMP 2064	
2213	JMP* 505	
2222	JMP* 505	
2061	JMP* 2315	
2315	12635	

LOCATION	INSTRUCTION	COMMENT
12635	CAS 167	
12636	JMP* 12700	
12637	JMP 12641	Check if it is a X.
12640	JMP* 12700	
12641	STA 12701	
12642	LDA 12702	
12643	CAS 101	
12644	JMP 12646	Check if GO1 after a G93.
12645	JMP 12650	a 693.
12646 12647	LDA 12701	
12650	JMP* 12700 LDA 160	Change SF to 1 when G01 after G93 and
12651	STA* 12703	X occurs.
12652	CRA	
12653	STA* 12704	
12654	LDA 12701	
12655	JMP* 12700	
12700	2235	
12701	Temp. storage for A	
12702	GO1 after G93 flag	
12703	10125	
12704	10126	

LOCATION	INCIDICTION	COMMENT
LOCATION	INSTRUCTION	COMMENT
2313	15625	
2777	223	
2776	160	
2212	CAS 223 (7777)	Compare G code.
2213	JMP* 505	
2214	JMP* 2313	
2215	JMP* 2326	
2216	LDA 133	
2217	STA 2300	
2220	LDA 2301	
2221	CAS 223 (93)	
2222	JMP* 505	
2223	JMP 2230	
2224	CAS 160 (2276) (70)	
2225	JMP 703	
2226	JMP 703	
2227	JMP 2253	
2253	CAS =4	
2254	JMP* 505	
2255	JMP* 505	

LOCATION	INSTRUCTION	COMMENT
2230	STA 2301	
2231	LDA 101 (1)	If G93, store
2232	STA 2300	1 in 2300.
2233	LDA 2301	
2234	JMP 703	
2326	12710	
12706	2301	
12707	15656	
12710	STA* 12706	
12711	LDA 12702	Check if GO1 after
12712	CAS 101	a G93.
12713	JMP* 12707	
12714	JMP* 12730	
12715	JMP* 12707	
12730	2216	
12731	15627	
12732	2300	
15626	JMP* 15666	
15666	12716	

LOCATION	INSTRUCTION	COMMENT
12716	CRA	
12717	STA 12702	
12720	JMP* 12731	
12740	LDA* 12732	
12741	CAS 101	
12742	JMP* 12730	Check if it a G93.
12743	JMP 12745	
12744	JMP* 12730	
12745	STA 12702	
12735	2124	
1274	an.	
12746	CRA	
12747	STA* 12703	
12750	LDA 12735	If G93, change scale factor.
12751	STA* 12704	
12752	JMP* 12730	
15656	LDA 160	
15657	STA* 15650	Set scale to 1.
15660	CRA 140040	
15661	STA* 15651	
15662	JMP* 15477	
15477	12740	

LOCATION	INSTRUCTION	COMMENT
15625	STA 15646	
15626	JMP* 15666	
15627	STA* 15650	
15630	LDA 1565 5	
15631	STA* 15651	
15632	LDA 15646	
15633	JMP* 15654	
15650	10125	
15651	10126	
15654	2230	
15652	000000	
15653	2124	

APPENDIX H
CINCINNATI TURNING CENTER

LOCATION	INSTRUCTION	COMMENT
502	DAC '17000,1	
773	DAC '14475	
775	DAC '5532	
776	DAC '5534	
777	DAC '14463	
5524	JMP* '777	JUMP on negative value check if character
14463	LDA INBF+169,1	before minus is an I.
14464 .	CAS '271	
14465	JMP *3	May be J, K.
14466	JMP *3	Yes
14467	JMP* '773	No
14470	CAS 1222	Check if it is a K.
14471	JMP* 1773	Not I, J, K.
14472	JMP *1	Yes
14473	LDA '260	It is a I, J, K, replace by a +.
14474	JMP* '776	prace by a +.
14475	LDA '200	Leave it as a
14476	JMP* 1775	

WATERVLIET ARSENAL INTERNAL DISTRIBUTION LIST

May 1976

	No. of Copies
COMMANDER	1
DIRECTOR, BENET WEAPONS LABORATORY	1
DIRECTOR, DEVELOPMENT ENGINEERING DIRECTORATE	1
ATTN: RD-AT	1
RD-MR	1
RD-PE	1
RD-RM	1
RD-SE	. 1
RD-SP	1
DIRECTOR, ENGINEERING SUPPORT DIRECTORATE	1
DIRECTOR, RESEARCH DIRECTORATE	2
ATTN: RR-AM	1
RR-C	1
RR-ME	1
RR-PS	1
TECHNICAL LIBRARY	5
TECHNICAL PUBLICATIONS & EDITING BRANCH	2
DIRECTOR, OPERATIONS DIRECTORATE	1
DIRECTOR, PROCUREMENT DIRECTORATE	1
DIRECTOR, PRODUCT ASSURANCE DIRECTORATE	1
PATENT ADVISORS	1

EXTERNAL DISTRIBUTION LIST

December 1976

1 copy to each

OFC OF THE DIR. OF DEFENSE R&E ATTN: ASST DIRECTOR MATERIALS THE PENTAGON WASHINGTON, D.C. 20315

CDR
US ARMY TANK-AUTMV COMD
ATTN: AMDTA-UL
AMSTA-RKM MAT LAB
WARREN, MICHIGAN 48090

PICATINNY ARSENAL
ATTN: SARPA-TS-S
SARPA-VP3 (PLASTICS
TECH EVAL CEN)
DOVER, NJ 07801

CDR FRANKFORD ARSENAL ATTN: SARFA PHILADELPHIA, PA 19137

DIRECTOR
US ARMY BALLISTIC RSCH LABS
ATTN: AMXBR-LB
ABERDEEN PROVING GROUND
MARYLAND 21005

CDR
US ARMY RSCH OFC (DURHAM)
BOX CM, DUKE STATION
ATTN: RDRD-IPL
DURHAM, NC 27706

CDR
WEST POINT MIL ACADEMY
ATTN: CHMN, MECH ENGR DEPT
WEST POINT, NY 10996

CDR HQ, US ARMY AVN SCH ATTN: OFC OF THE LIBRARIAN FT RUCKER, ALABAMA 36362 CDR
US ARMY ARMT COMD
ATTN: AMSAR-PPW-IR
AMSAR-RD
AMSAR-RDG
ROCK ISLAND, IL 61201

CDR
US ARMY ARMT COMD
FLD SVC DIV
ARMCOM ARMT SYS OFC
ATTN: AMSAR-ASF
ROCK ISLAND, IL 61201

CDR US ARMY ELCT COMD FT MONMOUTH, NJ 07703

CDR
REDSTONE ARSENAL
ATTN: AMSMI-RRS
AMSMI-RSM
ALABAMA 35809

CDR ROCK ISLAND ARSENAL ATTN: SARRI-RDD ROCK ISLAND, IL 61202

CDR
US ARMY FGN SCIENCE & TECH CEN
ATTN: AMXST-SD
220 7TH STREET N.E.
CHARLOTTESVILLE, VA 22901

DIRECTOR
US ARMY PDN EQ. AGENCY
ATTN: AMXPE-MT
ROCK ISLAND, IL 61201

BEST AVAILABLE COPY

EXTERNAL DISTRIBUTION LIST (Cont)

I copy to each

CDR
US NAVAL WPNS LAB
CHIEF, MAT SCIENCE DIV
ATTN: MR. D. MALYEVAC
DAHLGREN, VA 22448

DIRECTOR NAVAL RSCH LAB ATTN: DIR. MECH DIV WASHINGTON, D.C. 20375

DIRECTOR NAVAL RSCH LAB CODE 26-27 (DOCU LIB.) WASHINGTON, D.C. 20375

NASA SCIENTIFIC & TECH INFO FAC
PO BOX 8757, ATTN: ACQ BR
BALTIMORE/WASHINGTON INTL AIRPORT
MARYLAND 21240

REDSTONE ARSE
ATTN: DOCU & ALABAMA 35809

DEFENSE METALS INFO CEN BATTELLE INSTITUTE 505 KING AVE COLUMBUS, OHIO 43201

MANUEL E. PRADO / G. STISSER LAWRENCE LIVERMORE LAB PO BOX 808 LIVERMORE, CA 94550

DR. ROBERT QUATTRONE CHIEF, MAT BR US ARMY R&S GROUP, EUR BOX 65, FPO N.Y. 09510

2 copies to each

CDR US ARMY MOB EQUIP RSCH & DEV COMD ATTN: TECH DOCU CEN FT BELVOIR, VA 22060

CDR
US ARMY MAT RSCH AGCY
ATTN: AMXMR - TECH INFO CEN
WATERTOWN, MASS 02172

CDR WRIGHT-PATTERSON AFB ATTN: AFML/MXA OHIO 45433

CDR
REDSTONE ARSENAL
ATTN: DOCU & TECH INFO BR
ALABAMA 35809

12 copies

CDR
DEFENSE DOCU CEN
ATTN: DDC-TCA
CAMERON STATION
ALEXANDRIA, VA 22314

NOTE: PLEASE NOTIFY CDR, WATERVLIET ARSENAL, ATTN: SARWV-RT-TP, WATERVLIET, N.Y. 12189, IF ANY CHANGE IS REQUIRED TO THE ABOVE.